

Suiden

SPOT COOLER

(220V / 50Hz)

SS-22DD-8A

AUTOMATIC SWIVEL **MINI DRAIN**

SS-22ED-8A

MANUAL SWIVEL **MINI DRAIN**


INSTRUCTION MANUAL

Index

1. For your safety!	1
2. Product specification	2
3. Parts	3
4. Setup	4
• Placing the unit	4
• Attaching the cool air duct	4
• Attaching the hot air exhaust duct	5
• (Optional) Exhaust air duct extension	5
• (Optional) Cool air duct extension	6
• Connecting to a power source	7
• Trial operation	7
5. How to use	8
• Operating the unit	8
• Adjusting the direction of airflow	8
• The swivel function	9
• The drain tank	9
6. Safety devices	10
7. Maintenance and storage	11
• Cleaning the filter	11
• External maintenance	11
• Before storing the unit	12
8. Safety inspection	12
9. Troubleshooting	13
10. After service	14

△ Note:

Do not use the unit in places with gases or vapour containing hydrochloric acid, sulphuric acid, or any other corrosive substances.



Be sure to thoroughly read this manual to the end before commencing operation of the unit. Please also store this instruction manual in a place where it can be accessed by anyone who needs it at all times.

Thank you for purchasing this product from the world brand **SUIDEN**. Please use this product correctly after having thoroughly read this manual. After having finished reading, please store it in a place where it is easily accessed by people using the unit. If during use the unit malfunctions, or if something is unclear, please consult this manual.

1 FOR YOUR SAFETY!

Please do not operate the unit before carefully reading and understanding the content of this section. The items treated in this section are to ensure safe use of the unit and to beforehand prevent harm or injury to you and others. Further, to clarify the severity of the harm and injuries that can result from incorrect use, the items in this section are divided into two categories; Warnings and Caution. However, since the actions explained under caution also sometimes can cause severe harm, please follow all instructions in this section carefully regardless of category.



Warning: Incorrect use can cause death or severe injury.



Caution: Incorrect use can cause bodily harm or can damage the unit.

△ **Note:** Additional useful information other than warnings and caution.

● GENERAL CAUTION



Caution



Do not use the unit in any other way than is described in this manual.
* **Incorrect use can cause electric shock, short circuit, water leakage and other accidents, as well as can damage the unit.**



Do not use the unit on ships or in vehicles.
* **Use on ships or in vehicles can result in water leakage and a short circuit.**

● CARRYING / MOVING THE UNIT



Caution



When carrying, or moving the unit in any other way, please keep it balanced and adapt your movement to the shape and weight of the unit at all time.
* **If the unit is dropped, there is a risk of injury and other accidents.**



When packing the unit into and out of a vehicle, be sure to be 2 or more people to ensure safe operation.
* **If the unit is dropped, there is risk of physical injury and damage to the unit.**



If the unit is transported in a vehicle after it is unpacked, be sure to fasten it thoroughly with a rope or a strap.
* **If unfastened the unit can move unexpectedly and cause an accident.**

● TESTING AND OPERATING THE UNIT



Warning



Do not put wet hands on the plug, the switch or the electric wires.
* **This can cause electric shock and injury.**



Do not expose to water or oil.
* **Water or oil can cause a short circuit, electric shock and other accidents.**



Earth the unit securely, and use a earth leakage circuit breaker (bought separately).
* **When the unit is broken or has a short circuit, there is risk of electric shock.**



Use a 20A rated electrical outlet. Do not plug in any other electrical appliance in the same outlet.
* **If other appliances are connected in the same outlet at the same time, the outlet can overheat and catch fire.**



Please do not use the unit close to kerosene, gasoline, thinner, ether, paints or other flammable or explosive objects.
* **This can result in fire or explosion.**



Do not use the unit close to dust, gas or steam containing aluminium, magnesium, titanium or other flammable substances.
* **This can result in fire or explosion.**



Caution



Do not use the unit in a place with dust that is harmful to the human body.
* **If harmful dust sticks to the unit, there is risk of harmful dust dispersal when the unit is in operation.**



If the unit is not working properly, pull the plug immediately and turn it in for service or repair.
* **There is risk of electric shock or fire caused by a short circuit.**



















Do not expose your body to the cold air from the unit for an extended period of time.
* **Prolonged exposure can harm your health. Use the swivel function, or direct the duct so it does not point directly at you.**







Do not use the unit in vibrating or shaking places, or on slanting surfaces.
* **The unit can unexpectedly move or fall, causing accidents and injuries.**
* **Place the unit on a stabile level surface.**



Do not use the unit in places where it is exposed to water.
* **Contact with water can damage the insulation and cause electric shock, short circuit, fire and other accident and injuries.**

 Do not use in places with electrically conductive dust from Iron, carbon, casting, aluminium etc. * Electric shock or fire caused by a short circuit can occur.	 If you use the unit in a very dusty environment, make sure to clean the interior of the unit regularly. * Electric shock or fire caused by a short circuit can occur.
 Keep away from fire. * The unit can become deformed, causing short circuit and possibly fire.	 Do not put hands or fingers into the exhaust hole. * There is risk of injury.
 Do not use the unit if the cord or plug is damaged, or if the plug is loose in the socket. * Electric shock or fire caused by a short circuit can occur.	 If you use an extension cord, make sure to use one that meets the specified requirements. * There is risk of the cord overheating and catching fire.
 Do not let the plug get dirty or get exposed to metal objects while plugged. * There is risk of electric shock, short circuit and fire.	 Do not put heavy objects onto the electric cord. * If the cord gets damaged, there is risk of electric shock and fire.
 Do not use the extension cord while its is coiled or bundled together. * There is risk of the cord overheating and catching fire. * Make sure that the extension cord is extended before use.	 Do not use the unit in other than the stated operation conditions. * Since there is risk of electric shock, short circuit and malfunction, please use the unit within the suitable range: 25° (50% humidity) ~ 45° (40% humidity).
 Do not damage, process, nor bend, pull, twist or bundle the cord excessively. * If the cord gets damaged, there is risk of electric shock or fire.	 Do use electricity within the allowed range: 198V - 244V. * There is risk of electric shock and short circuit.
 Remove the plug from the electric outlet when the unit is not in use. * There is risk of burning and other injuries, electric shock, fire caused by short circuit etc.	 Do not use the unit in places with a lot of cutting oil or mineral oil. * They can cause the resin made parts of the unit to deteriorate, which can result in accidents and injuries.
 When you unplug the plug, be sure not to pull it by the cord, but to pull it out holding the plug directly. * There is risk of electric shock, short circuit and fire.	 Lock the caster wheels with the caster stoppers before starting to operate the unit. * The unit can start to move unexpectedly and cause accidents and injuries.

● MAINTENANCE


 Caution	
 Make sure that the unit is unplugged when in storage. * There is risk of injury and electric shock.	
 Disassemble, repair and reassemble is not to be attempted by anyone other than an authorized repairman/technician. * Inadequate or poor handling can result in fire, malfunction and injuries.	 All maintenance must be conducted while the unit is unplugged. * There is risk of electric shock and physical injuries.

2 PRODUCT SPECIFICATION


Model number		SS-22DD-8A	SS-22ED-8A
Automatic swivel		Yes	No
Power supply		Single phase 220V / 50Hz	
Cooling capacity		2.2kW	
Compressor / output		Air tight rotary model / 0,69kW output	
Air flow	Power output	200W	
	Cool air velocity	5,4m³/min (Strong) - 5,2m³/min (Weak)	
	Hot air velocity	9,8m³/min	
Dimensions (mm)		W 390 x D 430 x H 808 (Not including hot/cold air ducts)	
Operating condition		25°C (50%) - 45°C (40%)	Power factor 98%
Power consumption		0,80kW	Net weight 37kg
Starting current		15,5A	Running current 3,7A
Refrigerant		HCFC-22 (R22)	Refrigerant charge 320g
Power factor		96%	Remarks All values are measured during operation in 35°C / 60% humidity

3 PARTS

THE EXTERIOR



THE CONTROL PANEL




4 SETUP

Important: To ensure safety, read section one "1 For your safety!" first.

1. PLACING THE UNIT

Make sure that the unit is placed so that there is nothing blocking the front side filter, the cool air duct or the hot air exhaust duct.

There is only an air inlet on the front side, and the only air outlets are on the top, so the unit can be placed with the other sides directly against a wall, in a corner or in any other confined space.




Δ Note: Do not use the unit in places containing hydrochloric acid, sulphuric acid or any other corroding gas or steam.
* There is risk of gas leak or deterioration of performance.

2. ATTACHING THE COOL AIR DUCT

(1) ATTACHING THE DUCT ELBOW

- I. Insert the duct elbow into the elbow holder, fitting the attachment notch to the black mark on the inside of the holder.
- II. After you have inserted the duct elbow into the holder, fasten it so does not come loose by turning it to either side.

Δ Note:
Make sure that the duct elbow is correctly inserted into the holder. If the duct elbow is not attached evenly, reattach it correctly.




(2) ATTACHING THE COLD AIR DUCT

- I. Insert the cold air duct into the duct elbow, fitting the attachment peg on the duct to the attachment notch in the elbow, then turn it to the right.

Δ Be sure not to insert the end with the screws!


- II. Point the duct in the direction you want the air to blow in, fixing the duct elbow with your other hand.

* Please see page 8 for more information.



(3) REMOVING THE DUCT ELBOW



- I. Remove the cool air duct from the elbow.
- II. Turn the elbow until the attachment notch is aligned with the insertion mark.
- III. Remove the duct elbow by pulling it straight up from the holder.



● ADJUSTING THE FIRMNESS OF THE COLD AIR DUCT

If the cold air duct is too loose, it will just droop down, not maintaining the desired direction of the cool airflow. If this is the case, tighten the duct in the following manner.


- I. Grab both ends of the duct and stretch it until it is fully extended.
- II. Make the duct tighter by twisting the right end of the duct one or two times, fixing the left end of the duct with your other hand. Now the duct should maintain any shape desired by the user.



Stabilize with your left hand and twist towards your body with your right hand

3. ATTACHING THE HOT AIR EXHAUST DUCT

- I. Place the hot air exhaust duct onto the exhaust air vent, aligning the attachment guide marker (▼ 装取・固定) on the duct with the matching marker (△ 安装位置) on the attachment point on the top of the unit.
- II. Turn the duct clockwise until the attachment point marker (△ 安装位置) on the unit is aligned with the “fastened” (固定) marker on the duct and you hear a clicking sound.
- III. To remove the duct, turn it counter clockwise until the attachment guide marker (▼ 装取・固定) is aligned with the attachment point (△ 安装位置), and then lift it up vertically.



△ Note:

- * If something is dropped into the exhaust air vent, do not use a stick or similar object to try to retrieve it. You may damage internal parts and cause malfunction.
- * Do not block the exhaust air vent in any way. This will obstruct the function of the unit and cause malfunction.


OPTIONAL EXHAUST AIR DUCT EXTENSION

By attaching the optional hot air exhaust duct extension (Ø 175mm, length 4m) you can lead the hot air out of the room, preventing it from heating up the room.

Attach the hot air exhaust duct extension to the normal exhaust duct. Attaching the hot air exhaust duct extension is done in the same way as the optional cool air duct extension is attached. Therefore, please see instructions on attachment on the next page: “Optional cool air duct extension”.

△ Note:

- * If you will make an opening for the duct extension in the wall, make sure that it is done by a trained professional. Unprofessional installation can lead to water leakage and other problems.
- * Do not squeeze, press or bend the duct extension in a way that will obstruct the air flow.
- * If something is dropped into the exhaust air vent, do not use a stick or similar object to try to retrieve it. You may damage internal parts and cause malfunction.
- * Refrain from using the duct extension if the room temperature is higher than 40°C. There is risk of deterioration of the unit's cooling effect.




OPTIONAL COOL AIR DUCT EXTENSION

The cool air duct extension (Ø 125mm, length 5m) can be used when the unit can not be placed close to the workplace where it is needed.

• CUTTING THE COOL AIR DUCT EXTENSION

Cut the cool air duct extension according to required length in the following way.

- I. Make a hole in the duct extension where you want to cut it with a flat screwdriver or similar tool.
- II. Cut the duct extension all the way around using scissors or a side cutter.




• CHANGING THE DIAMETER

You can reduce the diameter of the cool air duct by twisting it to the left, thereby increasing the air flow velocity.

△ **Note:**



Be careful not to make the duct extension too narrow. This could cause deterioration of performance and malfunction.

Optional cool air duct extension





• ATTACHING THE COOL AIR DUCT EXTENSION TO THE COOL AIR DUCT

- I. Loosen the screws on the duct cap, and then remove the duct cap from the cool air duct.
- II. Mount the cool air duct extension to the cool air duct, narrow the end until the gap is completely sealed, then tighten the duct strap.
- III. Attach the accessory cool air duct extension cap onto the duct extension with glue.



• ATTACHING THE COOL AIR DUCT EXTENSION TO A CUT COOL AIR DUCT

- I. Cut the cool air duct.
- II. Mount the cool air duct extension to the cool air duct, narrow the end until the gap is completely sealed, then tighten the duct strap.
- III. Attach the accessory cool air duct extension cap onto the duct extension with glue.



• FASTENING THE COOL AIR DUCT EXTENSION

Hang the cool air duct extension with wires from the ceiling or fasten it securely to the wall.

△ **Note:**

Do not use the swivel function when the duct extension is attached.

* This will damage the swivel device.

3. CONNECTING TO A POWER SOURCE

△ **Note:** Do not connect any other electrical appliance to the same power source that the unit is connected to.

(1) ELECTRICAL WIRING


Make sure that no other electrical appliance is connected to the same power source as the unit.

(2) THE CIRCUIT BREAKER

Use a 10A, 30mA ≤ 0.1 sec. circuit breaker.

(3) CONNECTING THE UNIT TO A POWER SOURCE

Insert the plug into the power source.



4. TRIAL OPERATION

Turn on the power switch, the airflow adjustment switch and the swivel switch to make sure that everything works properly.

- I. The properties of all the switches are explained further in the next section "How to use".
- II. If the unit does not work properly, please consult page 13 "Trouble shooting" for further guidance.

△ **Note:** When you turn off the "COOL" airflow (the compressor) with the power switch and change it to "STOP" or "AIR", wait at least 3 minutes before turning the switch back to "COOL" again.

5 HOW TO USE

Important: To ensure safety, read section one "1 For your safety!" first.


1. OPERATING THE UNIT

(1) OPERATING THE POWER SWITCH (MODE)

- I. Open the control panel cover on the top of the unit.
- II. Turn the power switch on the control panel to "AIR" or "COOL".
 - * "AIR": The fan is working but not the compressor (No cool air is coming).
 - * "COOL": The fan and the compressor is working (Cool air is coming).

△ **Note:**

When you turn off the "COOL" option with the power switch and change it to "STOP" or "AIR", wait at least 3 minutes before turning the switch to "COOL" again.



(2) OPERATING THE AIRFLOW ADJUSTMENT SWITCH


Set the airflow to strong (H) or weak (L).

2. ADJUSTING THE DIRECTION OF AIRFLOW

The cool air duct can be adjusted, so please operate the unit after having pointed it in the desired direction.


● HORIZONTAL ADJUSTMENT

The cool air duct can be turned approximately 300°.




● VERTICAL ADJUSTMENT

The cool air duct is flexible and can be bent in any desired way within its possible range.



△ **Note:**

- I. Bend the cool air duct gently, firmly holding the duct elbow with your other hand.
 - * The duct can get damaged if forcedly bent too far.
- II. If something is dropped into the exhaust air vent, do not use a stick or similar object to try to retrieve it.
 - * You may damage internal parts and cause malfunction.
- III. Where the duct's attachment peg and the air vent's attachment notch align, the unit comes off. Therefore use the cool air duct within the indicated range.



3. THE SWIVEL FUNCTION

This function is only available on SS-22DD-8A.
Model SS-22ED-8A does not have a swivel function.


(1) OPERATING THE SWIVEL SWITCH (TURN)

Operate the swivel switch on the right of the control panel.

- * "ON": The cool air duct swivels to the right and left.
- * "OFF": The cool air duct does not move.

△ Note:

- * Make sure that nothing obstructs the swivel path of the cool air duct when the swivel function is turned on.
- * Do not use the swivel function with anything other than the standard cool air duct delivered with unit. If the swivel function is turned on, for example, when the duct extension is attached, the swivel device will be strained and can break.




(2) CHANGING THE POSITION OF THE SWIVEL

You can change the direction of the swivel in any desired direction.

- First turn off the swivel.
- Push the cool air duct lightly into desired position.

△ Note:

- * If the hot air exhaust duct is attached, the cool air duct can not swivel in that direction.
- * The duct elbow comes off at the point where the elbow attachment notch and the unit's attachment marker are aligned. Therefore, avoid swivel in that direction.




4. THE DRAIN TANK

(1) THE DRAIN TANK COLLECTS THE CONDENSED WATER

Part of the condensed water that appears in the upper cold part of the heat exchanger on the front of the unit vaporises when it passes through the warm lower part on the way down to the drain tank. In certain environments almost all water will vaporize, leaving nothing for the drain tank. This does not mean that the unit is not working.

△ Note:


- * The amount of condensed water that gathers in the drain tank varies depending on the temperature and humidity of the environment where the unit is used, as well as how clean or dirty the heat exchanger is. The amount of condensed water increases remarkably during rainy seasons and other times with high humidity, so be extra attentive at these times.
- * When the drain tank becomes full the water will start spilling out on the floor, so check the amount of water in the drain tank frequently and empty it before it gets full.
- * Since the condensed water in the drain tank will spill when the unit is moved, be sure to empty the tank first.



(2) DRAINING THE CONDENSED WATER WITH A HOSE

You can drain the condensed water directly to a drain or other desired place by attaching a hose onto the drain pipe. The inside diameter of the hose should be 16mm.

- I. Remove the drain tank.
- II. Attach the hose to the drain pipe, located on the upper left side of the drain tank compartment.
- III. Place the other end of the hose in a drain or other suitable place.





6 SAFETY DEVICES

(1) THE COMPRESSOR OVERLOAD RELAY

- I. The overload relay protects the compressor from overcurrents and overheating engine.
- II. The compressor overload relay is automatic. If the overload relay starts to work frequently (and the unit stops working), please take steps to eliminate the cause of the problem. If the cause is left unfixed, the unit can break down or malfunction.
Please consult "Trouble shooting" on page 13 for more information.

(2) THE FUSE

The fuse is located inside the service box. A 6.3A glass fuse is used.



△ **Note:**


When you change the fuse, please consult with a authorized electrician or your local suiden dealer.

7 MAINTENANCE AND STORAGE

Important: To ensure safety, read section one "1 For your safety!" first.

1. CLEANING THE FILTER

- I. Remove the filter by pulling it straight up.
- II. Clean off the dust from the filter with a vacuum cleaner.
- III. If the filter is dirty, it should be cleaned with water.
- IV. Reinstall the filter into the unit after it has dried completely.




OPTIONAL DUST FILTER

For customers who use the unit in locations with a lot of cotton, fibre, glass fibre and other kinds of dust.

If you are experiencing that the heat exchanger frequently clogs up and the "cool air" function stops working properly, we recommend you to replace the standard filter with the optional dust filter to solve this problem.

- * If the dust filter becomes clogged with dust the unit will not work properly. If that happens, clean the filter thoroughly.



OPTIONAL OIL MIST FILTER

For people who uses the unit in places with a lot of oil mist.

If you use the unit where there is a lot of oil mist in the air, we recommend that you replace the normal standard filter that comes delivered with the unit with a "Oil mist filter". The oil mist filter prevents deterioration of cooling effect caused by the heat exchanger becoming greasy, and prevents the condensed water from scattering.

2. EXTERNAL MAINTENANCE


- I. Wipe the ducts and other external parts clean with a dry piece of cloth, or a cloth with diluted neutral detergent.

△ Note:

Be very careful if you use thinner, benzine, chemicals or polishing powder or similar substances when cleaning the unit. You can easily damage the coating or cause malfunction.

3. BEFORE STORING THE UNIT

- I. Clean the filter and the exterior of the unit.
- II. Empty the drain tank and let it dry completely.
- III. Turn on "Ventilation" for approximately one hour to let the internal parts dry completely.
- IV. Cover the unit with a suitable cover to prevent dust from gathering.
- V. Store all the parts in a secure place so that nothing gets lost or damaged.
- VI. Clean the electric cord before storing it.



- * Regarding cleaning of the heat exchanger, the sirocco fan and other internal parts, please consult with your local dealer. If you clean the internal parts before storage, the unit can be used immediately afterwards.

△ Note:

Store the unit in a vertical standing position. Do not store it lying down.

- * If the unit is stored lying down, the compressor or other parts can break down or malfunction.

8 SAFETY INSPECTION

Important: To ensure safety, read section one "1 For your safety!" first.

To ensure safe operation, please perform the following inspections before use.
If any fault or malfunction is discovered, please take measures immediately.

Inspection	Measure
Is the electric cord damaged or deformed?	Change the cord after having consulted with an authorized electrician.
Is the plug deformed or broken?	Change the plug after having consulted with an authorized electrician.
Is the cord and the power source connected correctly?	If not, connect them correctly.
Are the ducts deformed or torn?	Change them for new ones.
Is the filter clogged with dust or dirt?	Clean the filter.
Is the filter installed correctly?	If not, install it correctly.
Is the filter torn or damaged?	Change it for a new one?
Is the fin of the heat exchanger broken?	Hand the unit in for inspection and repair at your local retailer.
Is the heat exchanger fin covered with dust or greasy dirt?	
Is the filter or cool air duct blocked?	Remove the obstructing object.
Is the drain tank installed correctly?	If not, Install it correctly.
Is the drain tank damaged?	Change it for a new drain tank.
Are the caster wheels worn out?	Change the caster wheels.
Are the caster stoppers working normally?	If not, change the caster wheels.
Are all the switches and buttons working properly?	If not, consult page 13 of this manual and follow the instructions. If the problem remains even after that, please consult with your local dealer regarding inspection and repair.
Is the unit emitting strange sounds or smells?	Please consult with your local dealer regarding inspection and repair.

9 TROUBLESHOOTING

Important: To ensure safety, read section one “1 For your safety!” first.

What's wrong?	What to check	Measure
I can not turn on the unit	Is there power supply? (The power could be off because of blackout etc.)	Turn the power switch to “STOP” until the power is back on again. If the switch is turned to “COOL” when the power comes back on, the fuse might blow.
	Is the plug correctly connected in the outlet?	Insert the plug correctly into the outlet.
	Is the electric cord broken or damaged in any other way?	Fix the cord if possible, otherwise change it for a new one.
	Is the electric fuse blown or the breaker down?	Please consult with an electrician or your local retailer.
	Is the overload relay running?	The unit will restore itself automatically. Wait for the unit to be restored, turn the switch to “STOP”, wait 3 minutes and then restart the unit.
The fuse blew or the breaker is down.	Is the capacity of the breaker sufficient?	Make sure that no other appliance is connected to the breaker or the branch circuit.
	Did you keep the cooler turned off for three minutes?	If you have turned off the unit, make sure to wait at least 3 minutes before turning on the “COOL” again. (This does not apply to “AIR”, which can be turned on immediately.)
	Is the voltage too low?	Consult with your electric company.
The unit turns itself on and off frequently (The overload relay)	Is the voltage too low?	Consult with your electric company.
The air from the unit is not cool	Is the power switch not set to “COOL”?	Set the switch to “COOL”.
	Is the filter or cold air duct blocked?	Remove the obstructing object.
	If the filter clogged with dust or dirt?	Clean the filter.
The cooling effect is weak	Is the room temperature too high? (Higher than 45°C is too high)	Improve the ventilation to lower the temperature of the room, or use the unit in a room that correspond to required conditions: 25°C - 45°C.
The cool air duct does not swivel (Only SS-22DD-8A)	Is the swivel switch turned off?	Turn the swivel switch to “ON”.
Water is leaking from the unit	Is the drain pipe clogged?	Clean the drain pipe.
	Is the drain tank full?	Empty the drain tank.
	Is the drain tank placed correctly?	If not, place it in its correct position.
	Is the drain tank damaged?	Repair it or change it for a new one.

If the problems do not get resolved by the above suggested measures, please consult with your local dealer.

10 AFTER SERVICE

Caution



Please use standard parts for maintenance and repair.

- * If you use spare parts other than standard parts, there is risk that they will not fit properly and can cause malfunction or accidents.
- * The same condition applies also to the case if Suiden spare parts are used in products from other companies.

• REPAIR

For questions regarding acquiring spare parts or regarding repair, please contact the store where you purchased the unit, after having prepared the product number, the manufacturer's serial number and the date of purchase.

For your safety

- * If you intend to use the unit to preserve food products, animals and plants, precision machines, art objects etc., please check the specific requirements of those objects carefully before you commence. Inaccurate or inappropriate use can cause the quality of the objects to deteriorate.
- * Sometimes it will be necessary to perform installation work and electric work to the unit. In these cases, contact your local dealer or an experienced professional. If the works are performed inadequately, there is risk of electric shock, fire or accidents.

Caution when using the manual

Thank you for buying this Suiden product.

This product is made to the specifications of you, the buyer. However, the content of the enclosed instruction manual is that of the standard model.

Please keep this in mind, and be cautious when using the product.