

Model	SJF-200L-1	SJF-200L-2	SJF-250L-1	SJF-250L-2	SJF-300L-1	SJF-300L-2	SJF-300L-3
Power supply (*)	Single phase 100V	Single phase 200V	Single phase 100V	Single phase 200V	Single phase 100V	Single phase 200V	3 phase 200V
Applicable duct dia.	230mm		280mm		320mm		
Fan blade	Diameter		250mm		288mm		
	Qty.		4		4		
Motor	Nominal output		200 W		400W		
	Poles		2P		2P		
Power consumption(50Hz)	100 W		160 W		345 W		300 W
Rated current	3A	1.6A	4.2A	2.2A	6.5A	3.3A	2.5A
Max. air volume(50Hz)	17 m ³ /min		28 m ³ /min		44 m ³ /min		
Noise level(50Hz)	65 dB		68.5 dB		71 dB		
Weight	8.7kg		10.5kg		14.5kg		
Dimensions (mm)	H360 × W382 × D380		H390 × W390 ×		H440 × W405 × D470		
Protective device	Thermal protector						-

*Other voltages available on demand.

*Design and specifications are subject to change without notice.

Model	SJF-200RS-1	SJF-200RS-2	SJF-250RS-1	SJF-250RS-2	SJF-300RS-1	SJF-300RS-2	SJF-300RS-3
Power supply(*)	Single phase 100V	Single phase 200V	Single phase 100V	Single phase 200V	Single phase 100V	Single phase 200V	3 phase 200V
Applicable duct dia.	230mm		280mm		320mm		
Fan blade	Diameter		250mm		288mm		
	Qty.		6		4		
Motor	Nominal output		350W		550W		
	Poles		2P		2P		
Power consumption(50Hz)	170 W	175 W	265 W	265 W	405 W	415 W	380 W
Rated current(50Hz)	3.0A	1.6 A	4.2 A	2.2 A	6.5 A	3.3 A	2.5 A
Max. air volum(50Hz)	20 m ³ /min		35 m ³ /min		50 m ³ /min		
Noise level(50Hz)	77.5 dB		83.5 dB		80 dB		
Weight	8 kg		9.1 kg		12.8 kg		
Dimensions (mm)	H300 × W305 × D337		H360 × W307 ×		H390 × W332 × D432		
Protective device	Thermal protector						-

*Other voltages available on demand.

*Design and specifications are subject to change without notice.

*Frequency is "50Hz".

Model	SJF-300C-1	SJF-300C-2	SJF-300C-3
Applicable duct diameter	320mm (Exhaust ducts are sold separately)		
Fan blade	Diameter		
	288 mm		
Fan blade	Quantity		
	6 blades		
Power supply (*)	Single phase 100V	Single phase 200V	3 phase 200V
Motor	Nominal output		
	400W		
Motor	Poles		
	2 poles		
Power consumption(50Hz)	425 W	410 W	400 W
Rated current(50Hz)	6.5 A	3.3 A	2.5 A
Max. air volum(50Hz)	52 m ³ /min		
Noise level(50Hz)	83.5 dB		
Weight	12.5 kg		
Dimensions (mm)	H: 390 × W: 330 × D: 423		
Protective device	Thermal protector		-

*Other voltages available on demand.

*Design and specifications are subject to change without notice.

Model	SJF-11	SJF-22
Features	Long distance air flow	
Power supply	Single phase 100V	3 phase 200V
Applicable duct diameter	200mm	
Fan blade	Diameter	
	300mm	
Fan blade	Quantity	
	12 Blades	
Motor	Nominal output	
	400W	
Motor	Poles	
	4P	
Power consumption(50Hz)	400W	360W
Rated current(50Hz)	5.6A	1.6A
Max. air volume(50Hz)	21.5 m ³ /min	
Weight	23.0kg	
Dimensions W x D x H (mm)	410 × 625 × 580	
Protective device	Thermal protector	-

1. SJF-22D1 is safe against a wider range of gases than SJF-22D2. Please contact us for consultation which model suits your need the be

2. This model does not have a protective device built into it, therefore make sure to connect it to an applicable motor breaker.

*Design and specifications are subject to change without notice.

Model	SJF-T604A	SJF-700A-3	SJF-600A-3	SJF-T506	SJF-408	SJF-T504	SJF-404
Applicable duct dia.	No	No	No	520mm	420mm	No	No
Fan blade	Diameter	600mm	710mm	600mm	490mm	400mm	500mm
	Quantity	4 Blades	6 Blades	9 Blades	6 Blades	8 Blades	4 Blades
Power supply	3 phase 200V						
Motor	Nominal output	1500W	2200W	1500W	750W	400W	750W
	Poles	4P	4P	4P	4P	4P	4P
Power consumption(50Hz)	870W	1750W	1040W	370 W	420 W	325 W	315 W
Rated current(50Hz)	8.5A	11.0A	6.5A	4.0A	2.8A	4.0A	2.8A
Max. air volume(50Hz)	500m ³ /min	740m ³ /min	480m ³ /min	147m ³ /min	78m ³ /min	220m ³ /min	163m ³ /min
Noise level(50Hz)	72 dB	87 dB	80 dB	79.5 dB	76.5 dB	67.5 dB	67.5 dB
Weight	83 kg	106 kg	79 kg	37 kg	26 kg	45 kg	35 kg
Dimensions W x D x H (mm)	1066×755×1177	1062×820×1292	920×690×1160	475×350×522	580×390×640	846×645×1014	718×590×858

*Design and specifications are subject to change without notice.

Model	SHC-35C-1	SHC-35C-3
Power	Single phase 100V	3 phase 200V
Speeds	Weak	Strong
Power consumption (50Hz)	52 W	70 W
Rated current(50H)	0.53 A	0.74 A
Max. air volume	71 m ³ /min	78 m ³ /min
Noise level(50Hz)	59.5 dB	61.5 dB
Weight	7.8 kg	7.7 kg
Power cable	0.75mm ² ×3-core (2P plug with earth clip) , length: 2m	0.75mm ² ×4-core, length: 2m
Dimensions (mm)	W524 × D248 × H497	W524 × D248 × H497
Protective device	Thermal protector	No*

* This models do not have a protective device built into it, therefore make sure to connect it to an applicable motor breaker.

* Design and specifications are subject to change without notice.

Model	SBF-400
Fan blade	Diameter
	Qty.
Power supply	3 phase 200V
Motor	Nominal output
	Poles
Power consumption(50Hz)	493 W
Max. air volum(50Hz)	60 m ³ /min
Weight	39 kg
Dimensions (mm)	W: 490 × D: 350 × H: 670
Protective device	This model does not have a protective device built into it, therefore make sure to connect it to an applicable motor breaker.

*Design and specifications are subject to change without notice.